

# UNINTERRUPTIBLE POWER SUPPLY -- UPS-1000 M



**Category:**

**Description:** UPS-1000M

**SPECIFICATIONS:** PRIMARY TECHNICAL  
PARAMETER  
Rated voltage: AC 220V  
Rated frequency: 50Hz/60Hz  
Input range: AC 165V-275V  
Output voltage: AC 220V±10%  
Transfer time: 4ms  
Battery type: 12V/7AH/1 PC  
(500M/650M)  
12V/7AH/2PCS (1000M/1200M)  
Back-up time: Over 15 minutes if  
use for one PC with a  
17' monitor (500M/650M); Over  
15 minutes if use for two PCS  
with 17' monitor (1000M/1200M)  
Charge time: ≤ 8 hours  
Operating temperature: -5℃~40℃  
Operating humidity: 10~90% RH,  
non condensing.  
Audio noise: < 40dBA  
Lightning protection: IEEE~587A  
DIMENSION & WEIGHT:  
Measurement(mm):300x120x191  
Packing Size(mm):360x180x285  
N.Weight(Kg):13.0

**Remarks :** FUNCTION &  
CHARACTERISTIC  
LED display  
CPU control  
AVR function  
Auto detect frequency  
Large loading capacity &  
compatibility  
Intelligent UPS management  
software  
Wide input voltage range  
Overload and output short circuit  
protection  
Over discharge function  
Build-in power purify circuit  
restrain distortion of lightning,  
pulse and miscellaneous waves  
etc.  
Buzzer alarm and sound silence  
function  
FAX/MODEM/TEL protection  
port

Kwaplah International, Inc

---

425 S.W Madison Avenue, Ste. U, Corvallis, OR 97333