

UNINTERRUPTIBLE POWER SUPPLY



Category: LINE-INTERACTIVE UPS

Description: UPS-1200D

SPECIFICATIONS: PRIMARY TECHNICAL PARAMETER

Rated voltage: AC 220V

Rated frequency: 50Hz/60Hz

Input range: AC 165V~275V

Output voltage: AC 220V~10%

Transfer time: 4ms

Battery type: 12V/7AH/1PC (500D/650D)

12V/7AH/2PCS (1000D/1200D)

Back-up time: Over 15 minutes if use for one PC with a 17' monitor (500D/650D);

Over 15 minutes if use for two PCS with 17' monitor (1000D/1200D)

Charge time: ≤8 hours

Operating temperature: -5℃~40℃

Operating humidity: 10-90% RH, non condensing.

Audio noise: < 40dBA

Lighting protection: IEEE~587A

N.Weight(Kg):13.0

Remarks : FUNCTION & CHARACTERISTIC

LCD display

CPU control

AVR function

Auto detect frequency

Large loading capacity & compatibility

Intelligent UPS management software

Cold start function

Wide input voltage range

Overload and output short circuit protection

Over discharge function

Build-in power purify circuit restrain distortion of lightning, pulse and miscellaneous waves etc.

Buzzer alarm and sound silence function

FAX/MODEM/TEL protection port

Kwaplah International, Inc

425 S.W Madison Avenue, Ste. U, Corvallis, OR 97333