

# UNINTERRUPTIBLE POWER SUPPLY – UPS-500D



**Category:** Line Interactive UPS

**Description:** UPS-500D

**SPECIFICATIONS:** PRIMARY TECHNICAL PARAMETER

Rated voltage: AC 220V

Rated frequency: 50Hz/60Hz

Input range: AC 165V~275V

Output voltage: AC 220V±10%

Transfer time: 4ms

Battery type: 12V/7AH/1Piece

Back-up time: Over 15 minutes if use for one PC with a 17' monitor

Charge time: ≤8 hours

Operating temperature: -5℃~40℃

Operating humidity: 10-90% RH, non-condensing.

Audio noise: < 40dBA

Lighting protection: IEEE~587A

**DIMENSION & WEIGHT:**

Measurement(mm):85x330x150

Packing Size(mm):420x150x250

N.Weight(Kg):6.8

**Remarks :** FUNCTION & CHARACTERISTICS

LCD display

CPU control

AVR function

Auto detect frequency

Large loading capacity & compatibility

Intelligent UPS management software

Cold start function

Wide input voltage range

Overload and output short circuit protection

Over discharge function

Build-in power purify circuit restrain distortion of lightning, pulse and miscellaneous waves etc.

Buzzer alarm and sound silence function

Fax/Tel/Modem protection ports

Kwaplah International, Inc

425 S.W Madison Avenue, Ste. U, Corvallis, OR 97333